

Colux: Heavy duty electric water cooler

Casing: Complete steel body (SS-304)

Refrigeration System: Fitted with world renowned high starting torque, high back pressure compressor, condenser and fan slightly over sized to ensure efficient working in high ambient temperature. SS-304 AISI cooling Coil metal bounded to in side water tank. Whole system hermetically sealed with R 22 Refrigerant.

Water Tank: Water system large capacity water tank made of heavy gauge stainless steel (SS- 304) AISI food grade material.

TAPS: High Quality Chrome Plated brass taps fitted with, or on sink separately.

Thermostat: High Quality water temperature control thermostat adjustable from 9 centigrade to 15 centigrade.

Insulation: Moisture proof and highly effective polyurethane thermal insulation out side water thank.

Voltage Rating: 380 to 400 volts 50 Hz A/C supply.



Technical Data

Model	Storage Capacity in Liter	Compressor Size	No of person use	Width	Depth	Height
CHDWC-200	200	2HP	200	36	28	55
CHDWC-300	300	2-1/2HP	300	36	32	55
CHDWC-500	500	3HP	500	40	36	60
CHDWC-700	700	5HP	700	46	44	60
CHDWC-1000	1000	7HP	1000	50	44	65
CHDWC-1200	1200	8HP	1200	55	48	65
CHDWC-1500	1500	12HP	1500	60	50	75

Note: The company reserves the right to change the specification for improvement of the products

with out prior notice. **Safety Devices:** Compressor over load protection. Low and high pressure swatch. Phase failure relay. Over currant protection switch. Suction and discharge line solenoid valve

Website: www.colux-industries.com Email: info@colux-industries.com

Colux Industries 145-B Small Industries Estate Sahiwal Pakistan

Tell: 92404558481 Cell, 943457430424