

Colux: Electric water heaters

Casing : Inner tanks is made of 2.52mm galvanized sheet to ensure its heavy construction tanks is checked at maximum recommended working pressure 150 Psi and outer shell made of 0.79mm pre painted galvanized sheet and finish with staving enamel paint for long life. The production is carried out under the supervision of qualified engineers

Insulation: World famous brand glass wool insulation used for better performance.

Heating element and thermostat: World famous brand thermo watt heating element and thermostat are used to ensure safety form Electric shock and energy saving.



Model	Capacity	Height in inches	Diameter in inches	Model	Capacity in gallons	Height in inches	Diameter in inches
EWH 6	6 Gallons	26 inch	13.4 inch	EWH 25	25 gallons	60 inch	16.4 inch
EWH 8	8 Gallons	30 inch	13.4 inch	EWH 35	35 gallons	68 inch	16.4 inch
EWH 10	10 Gallons	32 inch	13.4 inch	EWH 60	60 gallons	68 inch	21.4 inch
EWH 12	12 Gallons	32 inch	15 inch	EWH 80	80 gallons	75 inch	24 inch
EWH 15	15 Gallons	36 inch	15 inch	EWH 100	100 gallons	75 inch	26 inch
EWH 20	20 Gallons	36 inch	16.4 inch	EWH 150	150gallons	75 inch	28 inch

Special instruction for usage and installation of electric water heater.

1-Water connection to be connected with blue rubber pipe. 2-Hot water connection to be connected with red rubber pipe. 3- Don't switch on before filling up the water heater tank otherwise element will burn no claim will acceptable by company in this regard. 4 - Open the hot line to ensure water tank is full. 5 - Now switch on the water heater and set thermostat as desire.

Specification are subject to change with out any notice in view of continues improvements in the products.

Email: info@colux-industries.com Website: www.colux-industries.com

Colux Industries 145-B Small Industries Estate Sahiwal Pakistan

Tell: 92404558481 Cell: 923457430424