

Colux Electric water coolers

Casing: Complete steel body (SS 304)

Refrigeration System: Fitted with world renowned high starting torque, high back pressure compressor, condenser and fan slightly over sized to ensure efficient working in high ambient temperature. Copper cooling Coil Metal bounded

to out side water tank. Whole system hermetically sealed with R 22 Refrigerant.

Water System: All Copper/Brass. water system large capacity water tank made

of heavy gauge stainless steel, tank safety tested at (150 PSI) with recommended

maximum working pressure of (71 PSI) Fitted with High Quality Chrome Plated

Brass taps.

Thermostat: High Quality water temperature control thermostat adjustable from

6C to 15 C.

Insulation: Moisture proof and highly effective polyurethane insulation.

Voltage Rating: 220 volts 50 Hz A/C supply.



Model	Capacity in Liter/Hr	Compressor HP	Compressor Make	Number of people served	Dimension		
					Height	Width	Depth
CWC-25 P	25	1/6HP	Danfoss	30	40	21	19
CWC-35 P	35	1/4HP	Danfoss	35	42	21	19
CWC-45 P	45	1/3HP	Danfoss	45	46	21	19
CWC-65 P	65	1/2HP	Danfoss	65	48	21	19
CWC-80 P	80	¾ HP	Danfoss	80	50	22	20
CWC-100 P	100	1HP	Danfoss	100	60	27	20
CWC-150 P	150	1-1/2HP	Danfoss	150	65	34	22

Safety Devices: Compressor over load protection Time delay relay and circuit barker.

The Company reserves the right to change specifications without notice

Colux Industries 145-B Small Industries Estate Sahiwal Pakistan

Website: www.colux-industries.com **Email:** info@colux-industries.com

Telephone:92404558481 Cell:923457430424