

Colux Refrigerated dehumidifier.

50 L/Day to 120 L/Day

Colux Introduces refrigerating based moveable De-Humidifier, which is a continuous physical absorption system of moisture through the air. It helps in maintaining humidity up to certain desired level. The dehumidifiers are installed in houses, computer rooms, telephone exchanges hospitals, defense purposes as well as for commercial use to eliminate moisture caused mildew, warping humidity discomforts. All units have humidistat; witch maintains humidity as per requirement. The humidistat contains different levels to provide the desired humidity. The "environment humidity digital display Microcomputer" is distinct. It controls humidity and frost with automatic (ON/OFF switch). The buzzer will alarm when level is full. The humidity will appear on digital display of screen. Compressor has a 3-mintue delay at starting. Time may be extended to increase life of compressor. It has safe and reliable casing with complete metal design. It has beautiful look and is easy to handle. Wheels are installed under body witch facilitates is movement.



Models Are As Under.

Model	De-Humidityfying Capacity L/ Day	Operating range (°C)	Water storage capacity (Liters)
DHF-50	50	5~35	6
DHF-90	90	5~35	Continuous discharge
DHF-120	120	5~35	Continuous discharge

Note: Moisture removing capacity is based on room temperature at 80 F (26.7C) DB and 69.5 F (20.8.C) WB.

Specifications are subject to change without any notice.

Email: info@colux-industries.com Website: www.colux-industries.com

Colux Industries 145-B Small Industries Estate Sahiwal Pakistan

Tell:92404558481 Cell: 923457430424